



Connectivity

With a variety of options, like, communication cards, Expansion relays, SNMP and ambient monitoring applications, **Essential Power™** can be easily integrated into any environment and building management system.

Reliability

True-Online double conversion, pure sinewave output

Reliable digital power conversion architecture

Wide Range Input Window from 110 - 300Vac

Extended battery life I – U (DIN 41773)

Patented Backup Runtime Estimation on LCD

Ease of Service

Frontal access battery replacement

Clean and clear user-friendly display

Records event log and alarms up to 500

Personalization & Intelligent Self-diagnostic

Easy Firmware Flash Upgrade

Manual maintenance bypass switch (optional)

Battery Autonomy

EssentialPower™ 11RT	1kVA	2kVA	3kVA	6kVA	10kVA
UPS TYPE	UPS-EP001-11-103-2U UPS-EP001-11-103-2US	UPS-EP002-11-106-2U UPS-EP002-11-106-3US	UPS-EP003-11-106-2U UPS-EP003-11-106-4US	UPS-EP006-11-E-2U UPS-EP006-11-120-4U	UPS-EP010-11-E-3U
Battery Cabinet	CAB-EPBAT06-100-2U	CAB-EPBAT12-100-2U	CAB-EPBAT12-100-2U	CAB-EPBAT20-100-3U	CAB-EPBAT20-100-3U
Battery Type	7Ah / 9Ah	7Ah / 9Ah	7Ah / 9Ah	7Ah / 9Ah	7Ah / 9Ah
UPS	5 / 7	5 / 7	<3 / 4	N.A.	N.A.
UPS + 1 EPBATxx	27 / 35	25 / 32	15 / 20	6 / 8	3 / 4
UPS + 2 EPBATxx	54 / 69	50 / 64	31 / 40	17 / 22	8 / 11
UPS + 3 EPBATxx	83 / 106	77 / 98	49 / 63	30 / 39	15 / 19
UPS + 4 EPBATxx	114 / 146	96 / 135	68 / 87	44 / 57	23 / 29

EssentialPower™ 31RT	10kVA	15kVA	20kVA
UPS TYPE	UPS-EP010-31-E-3U	UPS-EP015-31-E-5U	UPS-EP020-31-E-5U
Battery Cabinet	CAB-EPBAT20-100-3U	CAB-EPBAT20-100-3U	CAB-EPBAT20-100-3U
Battery Type	7Ah / 9Ah	7Ah / 9Ah	7Ah / 9Ah
UPS	N.A.	N.A.	N.A.
UPS + 1 EPBATxx	3 / 4	<2 / 2	<1 / 1
UPS + 2 EPBATxx	9 / 12	5 / 7	3 / 4
UPS + 3 EPBATxx	17 / 22	9 / 12	6 / 8
UPS + 4 EPBATxx	25 / 32	14 / 18	9 / 12



2U
EPBAT12 | EPBAT06



3U
EPBAT20

* EssentialPower™ 11 RT: autonomies @ 100%load p.f 0.9
EssentialPower™ 31 RT: autonomies @ 100%load p.f 0.81

centiel

continuous power availability

centiel

continuous power availability

EssentialPower™



www.centiel.com



EssentialPower™ X1 RT

The Single Phase from 1kVA to 20kVA



SWISS

www.centiel.com



EssentialPower™, The Single Phase

EssentialPower™ is The On-Line, true double-conversion, single phase Uninterruptible Power Supply.

From 1 to 20kVA, EssentialPower™ provides the most flexible and reliable solution ideal for small network devices, servers, point-of-sale, work station clusters and light-industrial installations. EssentialPower™ satisfies any entry-level mission critical application demanding high availability and flexibility.

Flexibility for Any Application

From 2U to 5U, mono-mono or Tri-mono, EssentialPower™ can be used as standalone Tower or Rack-mounted UPS on any mission critical application.

EssentialPower™ offers built-in internal batteries from 1 to 6kVA, and the possibility to connect up-to 4 matching battery cabinets for autonomies of up to 4 hours.

Benefits

Standalone Tower or 19" Rack-mount configurations

Connectivity: USB, RS-232, potential-free contacts

EPO contact inputs for remote shutdown

Cold start

Parallel operation from 6kVA to 20kVA

Frequency converter operation (50 Hz or 60 Hz)

Connect up-to 4 battery modules to achieve hours of autonomy times



kVA=KW
FROM 6 TO 10 KW



Technical Datasheet

MODEL	EssentialPower™ 11RT				
	1kVA UPS-EP001-11-103-2U UPS-EP001-11-103-2US	2kVA UPS-EP002-11-106-2U UPS-EP002-11-106-3US	3kVA UPS-EP003-11-106-2U UPS-EP003-11-106-4US	6kVA UPS-EP006-11-E-2U UPS-EP006-11-E-20-4U	10kVA UPS-EP010-11-E-3U
GENERAL DATA					
Output rated power	1000VA /900W	2000VA /1800W	3000VA /2700W	6000VA /6000W	10000VA /10000W
Output power factor	0,9	0,9	0,9	1	1
Topology	Online double conversion				
Internal Batteries	YES	YES	YES	2U: N.A.; 4U: YES	N.A.
Parallel Configuration	N.A.	N.A.	N.A.	Up to 4 units	Up to 4 units
INPUT					
Voltage range	110-300 Vac (Single + G)	110-300 Vac (Single + G)	110-300 Vac (Single + G)	110-280 Vac (Single + G)	110-280 Vac (Single + G)
Frequency range	45-65Hz (auto sensing)		45-70Hz (auto sensing)		
Input power factor	≥ 0.99 @ 100% linear load				
Input Current Distorsion	≤ 6% (full load)	≤ 6% (full load)	≤ 6% (full load)	≤ 3% (full load)	≤ 3% (full load)
OUTPUT					
Output voltage	220/230/240 Vac (Single + G)			200/208/220/230/240 Vac (Single + G)	
Output voltage distortion	<3%@100% Linear Load; <5%@100% Non-Linear Load			<1%@100% Linear Load; <3%@100% Non-Linear Load	
Output voltage regulation	±1%				
Frequency range	±1Hz or ±3Hz (selectable)				
Crest factor	3:1				
Output waveform	Pure sine wave				
Overload Capacity Inverter	<105%continuous 106-120% for 30 seconds transfer to bypass. 121-150% for 10 seconds transfer to bypass.			<105%continuous 105-125% for 600 to 30 seconds transfer to bypass. 125-150% for 30 seconds to immediately transfer to bypass.	
EFFICIENCY					
Line Mode	Up to 92%	Up to 92%	Up to 92%	94%	94%
High Efficiency Mode	≥97%			≥98%	
BATTERY					
Type	VRLA (vented lead-acid)				
Battery Configuration	1x3x7Ah	1x6x7Ah	1x6x7Ah	E: External: 16/18/20 (std) 12-14 (opt) 120: 20x5Ah Internal	E: External: 16/18/20
Charging Current	2.1 A	1.5 A	1.5 A	2 A	2 A
Recharge time (to 90%)	4 hours				
FUNCTIONS					
Multi-Mode	Normal/ ECO/ CVCF				
Audible or Visual	Line failure/ Battery low/ Transfer to Bypass/ System Fault				
Full protection	Overload, Over temperature, Short circuit, Discharge, Overcharge				
DC start	Yes (standard)				
Programmable outlet	Yes (standard)	Yes (standard)	Yes (standard)	N.A.	N.A.
PHYSICAL					
Dimensions (WxHxD,mm)	2U: 440x88x405 2US: 440x88x405	2U: 440x88x600 3US: 440x132x432	2U: 440x88x600 4US: 440x176x432	2U: 440x88x685 3U: 440x176x685	3U: 440x132x685
Net Weight (kgs/lbs)	11.7/25.8	21.8/48.1	24.6/54.2	E: 11/24.25 120: 9/19.8 (5Ahx20)	11/24.25
ENVIRONMENTAL					
Operation Temperature	0-40°C / 32-104°F				
Operation Humidity	20-95%RH (without condensing)				
Altitude	1000m/3280ft without derating				
Noise Level	50dB @ 1-meter front		≤55dBA @ 1 meter ≤60dBA @ 1 meter		
COMMUNICATIONS					
Standard	RS-232, USB, EPO			USB/EPO	
Option	RS485 (Modbus), Dry Contact Relay, SNMP/WEB Card			RS232, RS485, Dry Contact Relay, SNMP/WEB Card	
User Interface	LCD: Input: Voltage/Frequency; Output: Voltage/Current/Frequency/Load %; Battery: Voltage/Autonomy/Temperature				
STANDARDS AND CERTIFICATIONS					
Safety	IEC / EN62040-1			IEC / EN62040-1, UL1778	
EMC	IEC / EN62040-2 (C2)			EN62040-2, EN61000-3-2, EN61000-3-3, FCC Class A	
Performance	IEC / EN62040-3				
Manufacturing	ISO 9001:2015, ISO 14001:2015 / CE, UL, cUL, FCC				

EssentialPower™ 31RT

MODEL	10kVA UPS-EP010-31-E-3U	15kVA UPS-EP015-31-E-5U	20kVA UPS-EP020-31-E-5U
GENERAL DATA			
Output rated power	10000VA /9000W	15000VA /13500W	20000VA /18000W
Output power factor	0,9		
Topology	Online double conversion		
Internal Batteries	NO		
Parallel Configuration	Up to 4 units		
INPUT			
Voltage range	277 - 485 Vac (3Ph + N + PE)		
Frequency range	45-65Hz (auto sensing)		
Input power factor	≥ 0.95 @ at linear load		
Input Current Distorsion	<3% at linear load		
OUTPUT			
Output voltage	220/230/240 Vac (Single + G)		
Output voltage distortion	<3%@100% Linear Load; <5%@100% Non-Linear Load		
Output voltage regulation	±1%		
Frequency range	±1Hz or ±3Hz (selectable)		
Crest factor	3:1		
Output waveform	Pure sine wave		
Overload Capacity Inverter	105% - 150% 600sec		
EFFICIENCY			
Line Mode	Up to 91%		
High Efficiency Mode	≥95%		
BATTERY			
Type	VRLA (vented lead-acid)		
Battery Configuration	E: External: 20		
Charging Current	2 A	4.5 A	4.5 A
Recharge time (to 90%)	External Battery Dependent		
FUNCTIONS			
Multi-Mode	Normal/ ECO/ CVCF		
Audible or Visual	Line failure/ Battery low/ Transfer to Bypass/ System Fault		
Full protection	Overload, Over temperature, Short circuit, Discharge, Overcharge		
DC start	Yes (standard)		
Programmable outlet	N.A.		
PHYSICAL			
Dimensions (WxHxD,mm)	440x132x680	440x220x720	440x220x720
Net Weight (kgs/lbs)	33 / 72.75	35 / 77.1	35 / 77.1
ENVIRONMENTAL			
Operation Temperature	0-40°C / 32-104°F		
Operation Humidity	20-95%RH (without condensing)		
Altitude	1000m/3280ft without derating		
Noise Level	50dB @ 1-meter front		
COMMUNICATIONS			
Standard	RS-232, EPO		
Option	USB, RS485 (Modbus), Dry Contact Relay, SNMP/WEB Card		
User Interface	LEDs + LCD: Input: Voltage/Frequency; Output: Voltage/Current/Frequency/Load %; Battery: Voltage/Autonomy/Temperature/Voltage/Autonomy/Temperature		
STANDARDS AND CERTIFICATIONS			
Safety	IEC / EN62040-1		
EMC	IEC / EN62040-2 (C2)		
Performance	IEC / EN62040-3		
Manufacturing	ISO 9001:2015, ISO 14001:2015 / CE, UL, cUL, FCC		



2U
1-6 kVA



3U
10kVA



4U
6kVA with Batteries



5U
15,20kVA

The information in this document is subject to change without notice and should not be construed as a commitment by Centiel S.A.
TDS_Rev1.0 19/09/18